

ACH580-01-026A-4

includes pump and fan features, such as control over the pump and the fan. consisting of unified height and depth, pipe cleaning, and filling operations. In addition to a load analyzer for load-optimized drive, motor, and process sizing, it was built with an energy efficiency counter and an energy optimizer. For quick parameter setting, it also comes with a Flash Drop tool.

Powerful and native communications HVAC communications protocols that are embedded save money by eliminating extra parts and wires. There are no extra costs or pointless options. Through embedded BACnetMS/TP and other HVAC protocols, you are able to manage applications, submit findings, read and write I/O settings, and carry out native diagnostics. Your teams don't need to be retrained for new terminology or features. Any controller's variation from our drive wouldn't even be noticeable.

Loop controllers standard For precise control of motors, fans, and pumps in HVAC applications, the drive offers a PID loop controller with two configuration options. Additionally, four external PID loop controllers are provided, which can be utilised for various external devices like dampers for changeable air volume or cooling and heating valves.

11kW Rated Inverter FLC 25 Amps Continuous Supply Power Supply 380 to 480 V, 3ph, 48 to 63 Hz Dimensions 394mmh, 125mmw, 227mmd ABB Frame size R2 (IP21) Weight 7.5kg With EMC filter built in as standard Inputs and Outputs: 2 Analogue I/Ps: (0/2-10v or 0/4-20mA or a Potenziometer) 2 Analogue O/P: (0-10v or 0-20mA) 6 Digital I/Ps 3 Digital O/Ps: (3 relay)



## ACH580-01-026A-4

Contact us for free full report

Web: <https://sumthingtasty.co.za/contact-us/>

Email: [energystorage2000@gmail.com](mailto:energystorage2000@gmail.com)

WhatsApp: 8613816583346

