



Abb 250 kw inverter

Abb 250 kw inverter

Keypad (HMI): Removable Assistant Control Panel ACH-AP-H included - multi-lingual with multi-line LCD Display. 2 x Analogue Inputs, 2 x Analogue Outputs, 6 x Digital Inputs, 3 x Relay Contact sets eldbus: BACnet MS/TP, Modbus RTU and N2. (Twin wire) Safe Torque Off: Terminals for dual channel SIL3/PLc STO. (Linked out as default)

Input Current: 430A put Voltage: 380 to 480V three phase $\pm 10\%$ at 50/60Hz put Fuse: 630A. gG (IEC) fuse can be used if operation time is less than 0.5s. See manual for uR or aR alternatives. Built in choke to minimise supply harmonics. EMC Compliance: to EN61800-3 1st Environment, C2 (Industrial and restricted domestic)

Cubicle Mount. Rated Ambient: 40°. Ventilation Space: Above: 200mm, Below: 300mm, Sides: 150mm, Front: Not Given Heat Loss at max output: 6036W. Mounting: via 4 x slotted holes at rear for M8 screws on 658mm x 345mm centres.

Contact us for free full report

Web: <https://sumthingtasty.co.za/contact-us/>

Email: energystorage2000@gmail.com

WhatsApp: 8613816583346

